## NSN 5950-00-156-0649

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-156-0649             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.250 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield brought out to terminal single component                  |
| Body Length:  |
| 1.650 inches  |
| Body Width:   |
| 1.500 inches  |
| Body Height:  |
| 1.950 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
|   |

## 4 single group **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

40 single group

### **Thread Size:**

0.112 inches single group

#### **Winding Operating Current:**

8.0 milliamperes dc single component single secondary

#### **Winding Operating Voltage:**

24.40 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

6 tab, solder lug

#### Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5950-00-156-0649

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0