NSN 5950-00-158-5163

Reactor - Page 1 of 1

A058b0



View Online at https://aerobasegroup.com/nsn/5950-00-158-5163

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.120 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.120 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 25.00 microhenries single component all winding |
| Frequency Rating: |
| 1.6 kilohertz single component |
| Body Length: |
| 1.710 inches |
| Body Outside Diameter: |
| 2.687 inches |
| Winding Quantity: |
| 2 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 35.0 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.0134 single component all winding |
| Terminal Type And Quantity: |
| 4 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |