## NSN 5950-00-159-7553

Power Transformer - Page 1 of 2



center group

center group

| View Online at https://aerobasegroup.com/nsn/5950-00-159-7553  |
|--|
| Reliability Indicator:   |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                                  |
| 4.740 inches single mounting facility single center group and 4.760 inches single mounting facility single |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                   |
| 4.490 inches single mounting facility single center group and 4.510 inches single mounting facility single |
| Overall Height:  |
| 5.500 inches   |
| Mounting Hole Diameter:  |
| 0.281 inches single group  |
| Frequency Rating:  |
| 5.0 kilohertz single component and 6.0 kilohertz single component  |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Winding Shielding Method:  |
| Internal shield grounded to inclosure and core single component  |
| Body Length:   |
| 5.500 inches   |
| Body Width:  |
| 5.250 inches   |
| Body Height:   |
| 4.970 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Flange single group and unthreaded hole single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component  |
| Winding Operating Current:   |
| 100.0 milliamperes dc single component single secondary  |
| Winding Operating Voltage:   |
| 9.60 ac kilovolts single component single secondary  |
| Terminal Type And Quantity:  |
| 2 turret and 4 solder stud   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |

No

Demilitarization:

## NSN 5950-00-159-7553

Power Transformer - Page 2 of 2



Fiig:

A058b0