

View Online at <https://aerobasegroup.com/nsn/5950-00-161-3195>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.813 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.340 inches

Body Width:

2.340 inches

Body Height:

3.880 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

35.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

112.00 ac volts and 114.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0