

View Online at <https://aerobasegroup.com/nsn/5950-00-161-4398>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.437 inches single mounting facility single center group

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.375 inches

Body Width:

2.875 inches

Body Height:

3.594 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.75 amperes dc single component single secondary

Winding Operating Voltage:

17.50 ac volts single component single secondary and 19.50 ac volts single component single secondary and 21.75 ac volts single component single secondary and 23.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0