

View Online at <https://aerobasegroup.com/nsn/5950-00-161-6419>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.750 inches

Body Width:

1.880 inches

Body Height:

2.880 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

60.0 milliamperes dc single component 2nd secondary

Winding Power Rating:

8.5 volts-amperes single component 3rd secondary

Winding Operating Voltage:

50.00 ac volts single component 3rd secondary

Special Features:

Primaries 1 and 2 not used at same time

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0