

View Online at <https://aerobasegroup.com/nsn/5950-00-163-1005>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.468 inches single mounting facility single center group and 2.531 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.843 inches single mounting facility single center group and 1.906 inches single mounting facility single center group

Frequency Rating:

47.5 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.219 inches

Body Width:

2.406 inches

Body Height:

Between 2.875 inches and 2.937 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

675.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

33.50 ac volts single component 1st secondary

Special Features:

1 primary winding; 5 secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0