

View Online at <https://aerobasegroup.com/nsn/5950-00-163-2344>

Reliability Indicator:

Not established

Frequency Rating:

5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.484 inches and 1.515 inches

Body Width:

Between 0.734 inches and 0.765 inches

Body Height:

Between 0.875 inches and 1.125 inches

Maximum Operating Temp:

85.0 degrees celsius

Distance Between Mounting Facility Centers:

1.000 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 milliamperes ac single component single secondary

Winding Operating Voltage:

10.00 ac volts single component single primary

Test Data Document:

30003-247as-c1872 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0