# NSN 5950-00-163-2368

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-163-2368

#### **Reliability Indicator:**

Not established

## Overall Length:

4.255 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

#### **Overall Height:**

3.062 inches

#### Overall Width:

3.562 inches

#### Frequency Rating:

400.0 hertz single component

## Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

# Transformer Winding Connection Type:

Wye-open delta and taylor

## Winding Shielding Method:

Internal shield brought out to terminal single component

#### Body Length:

3.875 inches

#### Body Width:

3.562 inches

#### Body Height:

3.062 inches

#### Inclosure Type:

Fully enclosed

#### Mounting Facility Quantity:

4 single group

#### Mounting Method:

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 12 secondary single component

#### Thread Size:

0.164 inches single group

# Winding Operating Current:

5.0 amperes dc single component 4th secondary

#### Winding Operating Voltage:

43.75 ac volts single component 2nd secondary

# Thread Series Designator:

Unc single group

# NSN 5950-00-163-2368

Power Transformer - Page 2 of 2



## Terminal Type And Quantity:

38 turret

## Specification Data:

30003-247asc1286-001featgone primary and fourteen secondary; secondaries have full wave rectified government specification

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A058b0