

View Online at <https://aerobasegroup.com/nsn/5950-00-165-3654>

Reliability Indicator:

Not established

Overall Length:

10.937 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.250 inches single mounting facility single center group

Overall Height:

4.937 inches

Overall Width:

7.937 inches

Mounting Hole Diameter:

0.406 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

End Application:

Forrestal class cv, spruance class dd (963), oliver perry class ffg, nimitz class cvn, wasp class lhd, tarawa class lha, emory s. Land class as, ticonderoga class cg (47), arleigh burke class ddg

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Winding Operating Current:

6.67 amperes ac single component single secondary

Winding Power Rating:

200.0 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.60 ac volts and 12.50 ac volts and 30.00 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0