

View Online at <https://aerobasegroup.com/nsn/5950-00-165-3654>

Reliability Indicator:

Not established

Overall Length:

10.937 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.250 inches single mounting facility single center group

Overall Height:

4.937 inches

Overall Width:

7.937 inches

Mounting Hole Diameter:

0.406 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

End Application:

Forrestal class cv, spruance class dd (963), oliver perry class ffg, nimitz class cvn, wasp class lhd, tarawa class lha, , emory s. Land class as, ticonderoga class cg (47), arleigh burke class ddg

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Winding Operating Current:

6.67 amperes ac single component single secondary

Winding Power Rating:

200.0 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.60 ac volts and 12.50 ac volts and 30.00 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0