

View Online at <https://aerobasegroup.com/nsn/5950-00-167-0310>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.802 inches single mounting facility single center group and 2.822 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group

Overall Height:

3.310 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.000 inches

Body Width:

3.440 inches

Body Height:

2.550 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 10 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

8.0 milliamperes ac single component 1st secondary

Winding Power Rating:

72.9 volts-amperes single component 3rd secondary

Winding Operating Voltage:

56.00 ac volts single component 2nd secondary

Special Features:

One primary winding; ten secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

33 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0