

View Online at <https://aerobasegroup.com/nsn/5950-00-168-4027>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.151 inches single mounting facility single center group and 3.182 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.671 inches single mounting facility single center group and 2.703 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 3.995 inches and 4.005 inches

Body Width:

3.500 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

0.45 ac volts single component single secondary and 0.50 ac volts single component single secondary and 0.60 ac volts single component single secondary and 0.75 ac volts single component single secondary and 0.85 ac volts single component single secondary and 1.00 ac volts single component single secondary and 1.20 ac volts single component single secondary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0