

View Online at <https://aerobasegroup.com/nsn/5950-00-169-8318>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.115 inches single mounting facility single center group and 2.135 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.615 inches single mounting facility single center group and 0.635 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

25.0 volt-ampere single component

**Body Length:**

Between 2.562 inches and 2.688 inches

**Body Width:**

Between 1.062 inches and 1.188 inches

**Body Height:**

Between 2.875 inches and 3.125 inches

**Maximum Operating Temp:**

85.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

1.0 amperes ac single component single secondary

**Winding Operating Voltage:**

25.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 turret

**Specification Data:**

30003-247asc2144 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0