

View Online at <https://aerobasegroup.com/nsn/5950-00-169-8318>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.115 inches single mounting facility single center group and 2.135 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches single mounting facility single center group and 0.635 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

25.0 volt-ampere single component

Body Length:

Between 2.562 inches and 2.688 inches

Body Width:

Between 1.062 inches and 1.188 inches

Body Height:

Between 2.875 inches and 3.125 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Specification Data:

30003-247asc2144 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0