## NSN 5950-00-169-8856

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-169-8856

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.125 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.438 inches single mounting facility single center group                 |
| Mounting Slot Width:  |
| 0.188 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 2.875 inches  |
| Body Width:   |
| 2.500 inches  |
| Body Height:  |
| 3.250 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and slot single group                                 |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Winding Operating Current:  |
| 2.0 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 115.00 ac volts single component single primary                           |
| Terminal Type And Quantity:   |
| 4 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <b></b>   |
| Demilitarization:   |
| No  |
| Fiig:   |
|   |

A058b0