# NSN 5950-00-172-0800

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-172-0800

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

4.343 inches single mounting facility single center group and 4.407 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.843 inches single mounting facility single center group and 3.907 inches single mounting facility single center group

#### **Inductance Type:**

Fixed

#### **Inductance Rating:**

7.00 millihenries single component single winding

#### Frequency Rating:

100.0 hertz single component and 120.0 hertz single component

#### **Body Length:**

Between 5.750 inches and 5.875 inches

#### **Body Width:**

Between 4.875 inches and 5.000 inches

#### **Body Height:**

Between 6.938 inches and 7.062 inches

#### Winding Quantity:

1 single component

# **Inclosure Type:**

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# **Rating Method:**

Electrical single component single winding

# Thread Size:

0.250 inches single group

# **Winding Operating Current:**

25.0 amperes dc single component single winding

# Dc Resistance Rating In Ohms:

0.028 single component single winding

#### **Criticality Code Justification:**

Feat

# **Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L00372

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

2 turret

# NSN 5950-00-172-0800

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0