NSN 5950-00-172-0800

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-172-0800

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.343 inches single mounting facility single center group and 4.407 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.843 inches single mounting facility single center group and 3.907 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

7.00 millihenries single component single winding

Frequency Rating:

100.0 hertz single component and 120.0 hertz single component

Body Length:

Between 5.750 inches and 5.875 inches

Body Width:

Between 4.875 inches and 5.000 inches

Body Height:

Between 6.938 inches and 7.062 inches

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thread Size:

0.250 inches single group

Winding Operating Current:

25.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.028 single component single winding

Criticality Code Justification:

Feat

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L00372

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 turret

NSN 5950-00-172-0800

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0