NSN 5950-00-173-1298

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-173-1298

| Thread Class (non-core): |
|---|
| Err-070 |
| |
| Reliability Indicator: Not established |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.685 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 5.050 inches |
| Body Width: |
| 2.800 inches |
| Body Height: |
| 3.800 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary and 5 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 13 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-173-1298

Power Transformer - Page 2 of 2



Fiig:

A058b0