

View Online at <https://aerobasegroup.com/nsn/5950-00-173-2440>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.484 inches single mounting facility single center group and 4.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.484 inches single mounting facility single center group and 3.516 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component and 6.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

6.000 inches

Body Width:

5.000 inches

Body Height:

6.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

22.9 amperes ac single component single primary

Winding Power Rating:

1.3 kilovolt-amperes single component single secondary

Winding Operating Voltage:

58.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 binding post

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0