## NSN 5950-00-173-4376

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-173-4376

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.969 inches single mounting facility single center group and 3.000 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.407 inches single mounting facility single center group and 2.438 inches single mounting facility single center group

#### **Overall Height:**

4.624 inches

### Frequency Rating:

45.0 hertz single component and 420.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### **Winding Shielding Method:**

Internal shield brought out to terminal single component

### **Body Length:**

Between 3.813 inches and 3.938 inches

### **Body Width:**

Between 3.250 inches and 3.375 inches

### **Body Height:**

Between 4.124 inches and 4.312 inches

### **Inclosure Type:**

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.190 inches single group

### **Winding Operating Current:**

10.0 amperes dc single component single secondary

### **Winding Operating Voltage:**

50.00 ac volts single component single secondary

### **Thread Series Designator:**

Unf single group

### **Terminal Type And Quantity:**

6 turret

### Shelf Life:

N/a

# NSN 5950-00-173-4376

Power Transformer - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A058b0