NSN 5950-00-174-3040

Power Transformer - Page 1 of 2



Vi	iew Online at https://aerobasegroup.com/nsn/5950-00-174-3040
o	verall Length:
1	1.750 inches
C	enter To Center Distance Between Mounting Facilities Parallel To Length:
8.	500 inches single mounting facility single center group
C	enter To Center Distance Between Mounting Facilities Parallel To Width:
7.	250 inches single mounting facility single center group
0	verall Height:
8.	625 inches
0	verall Width:
10	0.000 inches
M	ounting Hole Diameter:
0.	438 inches single group
F	requency Rating:
60	0.0 hertz single component
In	put-output Phase Relationship:
Si	ingle phase to single phase single component
M	aximum Transformer Power Rating:
3.	0 kilovolt-ampere single component
In	closure Type:
F	ully enclosed
M	ounting Facility Quantity:
4	single group
M	ounting Method:
FI	ange single group and unthreaded hole single group
С	ooling Type:
Fi	ns
С	ooling Method:
S	elf-cooled
W	inding Function And Quantity:
1	primary single component and 1 secondary single component
W	linding Operating Voltage:
45	50.00 ac pounds per hour wet single component single secondary
S	pecial Features:
D	ripproof, hi shock resistant
To	erminal Type And Quantity:
4	wire lead

Reference Number Differentiating Characteristics:

By mil-t-15108

Shelf Life:

N/a

Unit Of Measure:

NSN 5950-00-174-3040

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0