

View Online at <https://aerobasegroup.com/nsn/5950-00-174-3621>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.937 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.687 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Maximum Transformer Power Rating:

336.1 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.370 inches

Body Width:

2.370 inches

Body Height:

3.650 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

4.5 amperes ac single component 1st secondary

Winding Power Rating:

5.2 volts-amperes single component 2nd secondary

Winding Operating Voltage:

42.50 ac volts single component 1st secondary

Special Test Features:

Spec control 2326409

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

10 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by special test features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0