

View Online at <https://aerobasegroup.com/nsn/5950-00-174-3621>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.937 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.687 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-wye

**Maximum Transformer Power Rating:**

336.1 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

4.370 inches

**Body Width:**

2.370 inches

**Body Height:**

3.650 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

4.5 amperes ac single component 1st secondary

**Winding Power Rating:**

5.2 volts-amperes single component 2nd secondary

**Winding Operating Voltage:**

42.50 ac volts single component 1st secondary

**Special Test Features:**

Spec control 2326409

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Reference Number Differentiating Characteristics:**

As differentiated by special test features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A058b0