# NSN 5950-00-175-5909

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-175-5909

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.406 inches single mounting facility single center group and 3.468 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

#### **Overall Height:**

Between 4.250 inches and 4.562 inches

#### **Inductance Type:**

Fixed

#### **Inductance Rating:**

12.00 millihenries single component single winding

#### Frequency Rating:

90.0 hertz single component and 480.0 hertz single component

#### **Body Length:**

Between 4.125 inches and 4.250 inches

#### **Body Width:**

Between 3.625 inches and 3.750 inches

#### **Body Height:**

Between 3.812 inches and 4.000 inches

# **Winding Quantity:**

1 single component

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Rating Method:**

Electrical single component single winding

# Thready Qty Per Inch (tpi):

32 single group

# **Thread Size:**

0.190 inches single group

# **Winding Operating Current:**

10.6 amperes dc single component single winding

# Dc Resistance Rating In Ohms:

1.000 single component single winding

# **Thread Series Designator:**

Unf single group

### **Terminal Type And Quantity:**

2 turret

# NSN 5950-00-175-5909

Reactor - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0