## NSN 5950-00-175-5909

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-175-5909

## Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.406 inches single mounting facility single center group and 3.468 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

## **Overall Height:**

Between 4.250 inches and 4.562 inches

## Inductance Type:

Fixed

Inductance Rating:

12.00 millihenries single component single winding

## Frequency Rating:

90.0 hertz single component and 480.0 hertz single component

## Body Length:

Between 4.125 inches and 4.250 inches

#### Body Width:

Between 3.625 inches and 3.750 inches

#### **Body Height:**

Between 3.812 inches and 4.000 inches

## Winding Quantity:

1 single component

#### Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### Mounting Method:

Threaded stud single group

#### **Rating Method:**

Electrical single component single winding

#### Thready Qty Per Inch (tpi):

32 single group

#### Thread Size:

0.190 inches single group

#### Winding Operating Current:

10.6 amperes dc single component single winding

#### Dc Resistance Rating In Ohms:

1.000 single component single winding

#### **Thread Series Designator:**

Unf single group

#### **Terminal Type And Quantity:**

2 turret

# NSN 5950-00-175-5909

Reactor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

