NSN 5950-00-178-8414

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-178-8414

R	eliability Indicator:
N	lot established
С	enter To Center Distance Between Mounting Facilities Parallel To Length:
0	.344 inches single mounting facility single center group
С	enter To Center Distance Between Mounting Facilities Parallel To Width:
1	.000 inches single mounting facility single center group
Ir	npedance Rating In Ohms:
3	5000.0 single component single primary
F	requency Rating:
1	20.0 hertz single component
Ρ	rimary To Secondary Turn Ratio:
1	to 8-3/4 single component
В	ody Length:
3	.188 inches
В	ody Width:
1	.562 inches
В	ody Height:
3	.125 inches
lr	nclosure Type:
Н	lermetically sealed
N	Iounting Facility Quantity:
4	single group
N	Iounting Method:
Т	hreaded stud single group
v	Vinding Function And Quantity:
1	primary single component and 1 secondary single component
Т	hready Qty Per Inch (tpi):
4	0 single group
Т	hread Size:
0	.112 inches single group
v	Vinding Operating Current:
3	5.0 milliamperes dc single component single primary
Т	hread Series Designator:
U	Inc single group
Т	erminal Type And Quantity:
5	tab, solder lug
S	helf Life:
Ν	l/a
U	nit Of Measure:
D	emilitarization:
N	lo

NSN 5950-00-178-8414

Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

