

View Online at <https://aerobasegroup.com/nsn/5950-00-187-4361>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.562 inches single group

**Frequency Rating:**

54.0 hertz single component and 66.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Installation For Which Designed:**

Indoor nonportable

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

75.0 amperes ac single component single primary

**Winding Operating Voltage:**

500.00 ac volts single component single primary

**Test Data Document:**

81349-mil-i-1361 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bus (bar) conductor and 2 slotted lug

**Specification Or Standard:**

3 class and nss grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0