

View Online at <https://aerobasegroup.com/nsn/5950-00-187-4370>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.937 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.562 inches single group

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

8.500 inches

Body Width:

4.625 inches

Body Height:

10.156 inches

Installation For Which Designed:

Indoor nonportable

Inclosure Type:

Open

Mounting Facility Quantity:

4 1st group

Mounting Method:

Flange single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

5.0 amperes ac single component single secondary

Winding Operating Voltage:

600.00 ac volts single component single primary

Test Data Document:

81349-mil-i-1361 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded hole

Specification Or Standard:

3 class and nss grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0