## NSN 5950-00-190-1162

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-190-1162

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.156 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.156 inches single mounting facility single center group
Inductance Type:
Fixed
Inductance Rating:
60.00 millihenries single component all winding
Body Length:
1.500 inches
Body Width:
1.500 inches
Body Height:
2.000 inches
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
A single group
4 single group
Mounting Method:
Mounting Method:
Mounting Method: Threaded hole single group
Mounting Method: Threaded hole single group Rating Method:
Mounting Method: Threaded hole single group  Rating Method: Electrical single component single winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.500 single component all winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.500 single component all winding Thread Series Designator:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.500 single component all winding Thread Series Designator: Unc single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity:

--

**Unit Of Measure:** 

## NSN 5950-00-190-1162

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0