

View Online at <https://aerobasegroup.com/nsn/5950-00-190-5773>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.115 inches single mounting facility single center group and 2.135 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 2.677 inches and 2.697 inches

Body Width:

Between 2.302 inches and 2.322 inches

Body Height:

Between 3.052 inches and 3.072 inches

Maximum Operating Temp:

160.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Voltage:

8.00 ac volts single component single secondary and 12.50 ac volts single component single secondary and 17.50 ac volts single component single secondary and 18.50 ac volts single component single secondary and 19.00 ac volts single component single secondary and 21.00 ac volts single component single secondary and 21.50 ac volts single component single secondary and 22.50 ac volts single component single secondary and 27.50 ac volts single component single secondary and 32.00 ac volts single component single secondary and 40.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A058b0