NSN 5950-00-193-8645

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-193-8645

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 5.625 inches single mounting facility single center group Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Current: 6.0 amperes ac single component 4th secondary Winding Operating Current: 6.0 amperes ac single component 1st secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Firminal Type And Quantity: <t< th=""></t<>
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 5.625 inches single mounting facility single center group Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 1st secondary Midning Operating Voltage: 852.00 ac volts single component 1st secondary Hermetial Type And Quantity: 1 4 standoff insulator
 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 5.625 inches single mounting facility single center group Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Center To Center Distance Between Mounting Facilities Parallel To Width: 5.625 inches single mounting facility single center group Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Operating Current: 6.0 anperes ac single component 1st secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Fleminal Type And Quantity: 14 standoff insulator
 5.625 inches single mounting facility single center group Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Operating Current: 6.0 amperes ac single component 1st secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Farminal Type And Quantity: 14 standoff insulator
Frequency Rating: 57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Winding Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
57.0 hertz and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Hornetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Body Height: 7.875 inches Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Vinding Function And Quantity: 1 primary and 4 secondary single component Minding Operating Current: 6.0 amperes ac single component 1st secondary Kinding Operating Voltage: 852.00 ac volts single component 1st secondary 14 standoff insulator Shelf Life:
Winding Shielding Method:Internal shield grounded to inclosure single componentBody Length:5.875 inchesBody Width:4.750 inchesBody Height:7.875 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Flange and unthreaded hole single groupWinding Operating Current:6.0 amperes ac single component 4th secondaryWinding Operating Voltage:852.00 ac volts single component 1st secondaryTerminal Type And Quantity:14 standoff insulatorShelf Life:
Internal shield grounded to inclosure single component Body Length: 5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator
Body Length:5.875 inchesBody Width:4.750 inchesBody Height:7.875 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Flange and unthreaded hole single groupWinding Function And Quantity:1 primary and 4 secondary single componentWinding Operating Current:6.0 amperes ac single component 4th secondaryWinding Operating Voltage:852.00 ac volts single component 1st secondary14 standoff insulatorShelf Life:
5.875 inches Body Width: 4.750 inches Body Height: 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Body Width:4.750 inchesBody Height:7.875 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Flange and unthreaded hole single groupWinding Function And Quantity:1 primary and 4 secondary single componentWinding Operating Current:6.0 amperes ac single component 4th secondaryWinding Operating Voltage:852.00 ac volts single component 1st secondaryTerminal Type And Quantity:14 standoff insulatorShelf Life:
 4.750 inches Body Height: 7.875 inches 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator
Body Height:7.875 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Flange and unthreaded hole single groupWinding Function And Quantity:1 primary and 4 secondary single componentWinding Operating Current:6.0 amperes ac single component 4th secondaryWinding Operating Voltage:852.00 ac volts single component 1st secondaryTerminal Type And Quantity:14 standoff insulatorShelf Life:
 7.875 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator
 Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: primary and 4 secondary single component Winding Operating Current: 0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Mounting Method:Flange and unthreaded hole single groupWinding Function And Quantity:1 primary and 4 secondary single componentWinding Operating Current:6.0 amperes ac single component 4th secondaryWinding Operating Voltage:852.00 ac volts single component 1st secondaryTerminal Type And Quantity:14 standoff insulatorShelf Life:
 Flange and unthreaded hole single group Winding Function And Quantity: primary and 4 secondary single component Winding Operating Current: 0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 Winding Function And Quantity: 1 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 primary and 4 secondary single component Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 Winding Operating Current: 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
 6.0 amperes ac single component 4th secondary Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Winding Operating Voltage: 852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
852.00 ac volts single component 1st secondary Terminal Type And Quantity: 14 standoff insulator Shelf Life:
Terminal Type And Quantity: 14 standoff insulator Shelf Life:
14 standoff insulator Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0