

View Online at <https://aerobasegroup.com/nsn/5950-00-194-6787>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

3.250 inches

Body Height:

2.641 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.0 amperes ac single component single secondary and 6.0 milliamperes ac single component single secondary

Winding Operating Voltage:

2.50 ac volts single component single secondary and 735.00 ac volts single component single secondary

Special Features:

Terminal bushings are porcelain the 2.5 v winding and the 735 winding have a common terminal

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0