

View Online at <https://aerobasegroup.com/nsn/5950-00-194-8992>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.859 inches single mounting facility single center group and 3.890 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.421 inches single mounting facility single center group and 2.453 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.625 inches

Body Width:

3.187 inches

Body Height:

5.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

16.0 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0