

View Online at <https://aerobasegroup.com/nsn/5950-00-195-5444>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

5.500 inches

Body Width:

4.500 inches

Body Height:

4.625 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

200.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

200.00 ac volts single component single primary and 208.00 ac volts single component single primary and 235.00 ac volts single component single primary

Terminal Type And Quantity:

10 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0