## NSN 5950-00-195-9818

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-195-9818

| •   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.062 inches single mounting facility single center group                 |
| Overall Height:   |
| 3.000 inches  |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 10.00 henry single component single winding                               |
| Body Length:  |
| 1.875 inches  |
| Body Width:   |
| 1.625 inches  |
| Body Height:  |
| 2.500 inches  |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Rating Method:  |
| Electrical single component single winding                                |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 55.0 milliamperes dc single component single winding                      |
| Dc Resistance Rating In Ohms:   |
| 400.000 single component single winding                                   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 2 standoff, solder lug  |
| Shelf Life:   |

N/a

## NSN 5950-00-195-9818

Reactor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A058b0