NSN 5950-00-196-0824

Power Transformer - Page 1 of 2



| V | iew Online at https://aerobasegroup.com/nsn/5950-00-196-0824 |
|----|---|
| R | Reliability Indicator: |
| N | lot established |
| С | Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1 | .500 inches single mounting facility single center group |
| С | Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1 | .000 inches single mounting facility single center group |
| F | requency Rating: |
| 4 | 5.0 hertz single component and 66.0 hertz single component |
| Ir | nput-output Phase Relationship: |
| S | ingle phase to single phase single component |
| В | ody Length: |
| 2 | .090 inches |
| В | ody Width: |
| 1 | .650 inches |
| В | ody Height: |
| 2 | .530 inches |
| Ir | nclosure Type: |
| Н | lermetically sealed |
| N | Iounting Facility Quantity: |
| 4 | single group |
| N | Iounting Method: |
| Т | hreaded stud single group |
| v | Vinding Function And Quantity: |
| 2 | primary single component and 1 secondary single component |
| т | hready Qty Per Inch (tpi): |
| 3 | 2 single group |
| т | hread Size: |
| 0 | .138 inches single group |
| v | Vinding Operating Current: |
| 2 | 80.0 milliamperes ac single component single secondary |
| v | Vinding Operating Voltage: |
| 5 | 3.50 ac volts single component single secondary |
| т | hread Series Designator: |
| U | Inc single group |
| т | erminal Type And Quantity: |
| 7 | wire hook |
| S | helf Life: |
| N | l/a |
| U | Init Of Measure: |
| | |
| D | emilitarization: |
| N | lo |
| | |

NSN 5950-00-196-0824

Power Transformer - Page 2 of 2

Fiig: A058b0

