## NSN 5950-00-196-7232

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-196-7232

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.813 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.438 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.250 inches single group   |
| Frequency Rating:   |
| 45.0 hertz single component and 420.0 hertz single component              |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 3.375 inches  |
| Body Width:   |
| 2.750 inches  |
| Body Height:  |
| 2.875 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 1 primary single component and 3 secondary single component               |
| Winding Operating Current:  |
| 600.0 milliamperes dc single component 2nd secondary                      |
| Winding Operating Voltage:  |
| 50.00 ac volts single component 3rd secondary                             |
| Terminal Type And Quantity:   |
| 11 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
|   |

A058b0