NSN 5950-00-197-0382

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-197-0382

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.875 inches single mounting facility single center group
Mounting Slot Width:
0.281 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
6.625 inches
Body Width:
5.250 inches
Body Height:
4.375 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component
Winding Power Rating:
750.0 volts-amperes single component single secondary
Winding Operating Voltage:
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity:
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity:
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug Shelf Life:
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a Unit Of Measure:
95.00 ac volts single component single secondary and 115.00 ac volts single component single secondary Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: