

View Online at <https://aerobasegroup.com/nsn/5950-00-198-5887>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Primary shield grounded to inclosure and secondary shield brought out to terminal single component

Body Length:

3.938 inches

Body Width:

3.938 inches

Body Height:

4.938 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

900.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

750.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0