## NSN 5950-00-198-5887

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-198-5887

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Primary shield grounded to inclosure and secondary shield brought out to terminal single component

#### **Body Length:**

**3.938** inches

#### **Body Width:**

**3.938** inches

### **Body Height:**

**4.938** inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

2 primary single component and 4 secondary single component

### Thready Qty Per Inch (tpi):

20 single group

#### **Thread Size:**

0.250 inches single group

### **Winding Operating Current:**

900.0 milliamperes ac single component 3rd secondary

### **Winding Operating Voltage:**

750.00 ac volts single component 1st secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

14 standoff insulator

### Shelf Life:

N/a

# NSN 5950-00-198-5887

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0