

View Online at <https://aerobasegroup.com/nsn/5950-00-198-8511>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.312 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

7.500 inches

Body Width:

7.000 inches

Body Height:

7.000 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

353.0 milliamperes ac single component single secondary

Winding Operating Voltage:

210.00 ac volts single component single primary and 220.00 ac volts single component single primary and 230.00 ac volts single component single primary and 240.00 ac volts single component single primary and 250.00 ac volts single component single primary

Terminal Type And Quantity:

6 screw and 3 standoff, screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0