

View Online at <https://aerobasegroup.com/nsn/5950-00-198-8704>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.000 inches

Body Width:

1.062 inches

Body Height:

1.062 inches

Distance Between Mounting Facility Centers:

1.500 inches single mounting facility single center group

End Application:

Cvn 68 class reactor fill auxiliary system, sturgeon class ssn (637), nimitz class cvn, los angeles class ssn (688), fire pumps, forrestal class cv, fire control system, missile mk 74 (fcs), ticonderoga class cg (47), spruance class dd (963)

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Criticality Code Justification:

Feat

Winding Operating Voltage:

450.00 ac volts single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

5 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0