

View Online at <https://aerobasegroup.com/nsn/5950-00-199-1712>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

5.312 inches

**Body Width:**

4.562 inches

**Body Height:**

5.688 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

4.40 ac kilovolts single component 2nd secondary

**Special Features:**

Internal shield around low voltage winding

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

6 standoff insulator and 1 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0