

View Online at <https://aerobasegroup.com/nsn/5950-00-199-2185>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.688 inches

Body Width:

3.188 inches

Body Height:

4.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

5.0 amperes ac single component 1st secondary

Winding Operating Voltage:

5.00 ac kilovolts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 standoff, screw and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0