

View Online at <https://aerobasegroup.com/nsn/5950-00-199-2293>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

7.875 inches

Body Width:

5.750 inches

Body Height:

8.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

65.0 amperes ac single component single secondary

Winding Operating Voltage:

34.00 ac volts single component single secondary

Special Features:

Marked p1 p2 s1 s2 on top of case and h pot 700 v rms w/schematic on front

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0