NSN 5950-00-199-2576

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-199-2576

| Reliability Indicator: | | | |
|-------------------------------------------------------------|--|--|--|
| Not established | | | |
| Overall Length: | | | |
| 2.344 inches | | | |
| Overall Height: | | | |
| 3.821 inches | | | |
| Overall Width: | | | |
| 2.344 inches | | | |
| Frequency Rating: | | | |
| 400.0 hertz single component | | | |
| Input-output Phase Relationship: | | | |
| Single phase to single phase single component | | | |
| Winding Shielding Method: | | | |
| Internal shield grounded to inclosure single component | | | |
| Body Length: | | | |
| 2.344 inches | | | |
| Body Width: | | | |
| 2.344 inches | | | |
| Body Height: | | | |
| 2.844 inches | | | |
| Distance Between Mounting Facility Centers: | | | |
| 1.500 inches single mounting facility single center group | | | |
| Inclosure Type: | | | |
| Hermetically sealed | | | |
| Mounting Facility Quantity: | | | |
| 2 single group | | | |
| Mounting Method: | | | |
| Threaded stud single group | | | |
| Winding Function And Quantity: | | | |
| 1 primary single component and 2 secondary single component | | | |
| Thready Qty Per Inch (tpi): | | | |
| 24 single group | | | |
| Thread Size: | | | |
| 0.190 inches single group | | | |
| Winding Operating Current: | | | |
| 700.0 milliamperes ac single component 1st secondary | | | |
| Winding Operating Voltage: | | | |
| 6.15 ac pounds per hour wet single component 1st secondary | | | |
| Thread Series Designator: | | | |
| Unc single group | | | |
| Terminal Type And Quantity: | | | |

6 standoff insulator

NSN 5950-00-199-2576

Power Transformer - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0