

View Online at <https://aerobasegroup.com/nsn/5950-00-203-1204>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.438 inches

Body Width:

2.750 inches

Body Height:

4.500 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

103.50 ac volts single component single primary and 109.25 ac volts single component single primary and 115.00 ac volts single component single primary and 120.75 ac volts single component single primary and 126.50 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0