NSN 5950-00-203-1291

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-203-1291

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.188 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.188 inches |
| Body Width: |
| 2.938 inches |
| Body Height: |
| 3.688 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Voltage: |
| 2.50 ac volts single component single secondary and 3.00 ac volts single component single secondary and 5.00 ac volts single component |
| single secondary and 7.10 ac volts single component single secondary and 8.50 ac volts single component single secondary and 9.50 ac |
| volts single component single secondary and 12.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 11 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |