

View Online at <https://aerobasegroup.com/nsn/5950-00-204-7982>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.090 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.090 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

Mounting Hole Diameter:

0.193 inches single group and 0.199 inches single group

Frequency Rating:

50.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.820 inches

Body Width:

2.750 inches

Body Height:

2.250 inches

Maximum Operating Temp:

120.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Operating Voltage:

85.00 ac volts single component single secondary

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0